

Weight classes: 3000, 4000, 5000, 6000, 7000, and 12000.

Max tire size: 3000 – 13.6”

4000 – 15.5”

5000 – 16.9”

6000, 7000, 12000 – 18.4”

2. Front weights shall not exceed more than 24” beyond the center of the front frames outmost casting. Rear weights not to exceed 24” behind center rear axle.
3. Rigid draw bar must not exceed 20” in height, nor can be closer than 18” from the center of the rear axle.
4. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires or foot feeds allowed. Decision of the track judge is final. 20% over RPMS will be allowed. ALL TRACTORS RPM LIMITS ENFORCED.

NEAR STOCK

1. Must be 1957 or older – low gear only.
Weight classes: 4000, 5000, 6000, and 7000. Must be within manufactures hp and RPMS.
2. Engine, stock block, head, manifold, carb (by part #), no add-on parts not in original parts book. No electronic ignitions, stock coil only. Stock hp and rpms.
3. Tractors must have original, or as close to original size tires, rims, cut-down steel is ok. No 18.4” tires will be allowed.
4. Original hitch/drawbar hole must be no closer than 32” from center of rear axle, allowances will be made on certain models, maximum height 20” and must be rigid.
5. Tractors must have stock appearance.
6. No cut or sharpened tires.
7. Must have original air cleaner, if one is used.
8. No weight brackets. Weights will only be allowed if placed on wheels.
9. No radial tires.
10. ALL TRACTORS WILL BE DYNO’ED AND RPM LIMITS WILL BE ENFORCED.

8 MPH PACE

1. Must be 1957 or older.
Weight classes: 3750, 4750, 5750, 6750.
Max tire size: 18.4”
2. Must run stock block, transmission, rear-end, sheet metal, etc.
3. Cut tires are allowed.
4. Wheelie bars, kill switch and fenders MANDATORY!
5. RPM’s over 20% must have safety equipment (safety blanket, scatter shield, steel flywheel, fan shroud or side shields, etc.)
6. NO TROPHIES, 100% PAYBACK FOR FIRST, SECOND and THIRD PLACING.

Rigid draw bar MUST
support weight of tractor

ROSHOLT AREA THRESHERMEN FARM TRACTOR RULES

Farm Pulling Rules

1. Any year farm tractor allowed.
 2. Anyone caught tampering with another tractor will be disqualified.
 3. Tractors must be operated in a safe manor at all times.
 4. No crawlers, tire chains or duals.
 5. Hitch point can not be higher than 20" or closer than 18" from center of rear axle, all 3-point hitches must be locked from moving! **ABSOLUTELY NO FLOATING DRAWBARS!!!!**
 6. Any tractor violating track boundaries must take distance at that point.
 7. Tractors must stop upon red flag or will be disqualified. If track stops pull for any reason, puller must take that distance.
 8. Any drivers between 14/18 years old **MUST** have parental signature and tractor safety class certificate with them, **NO EXCEPTIONS!**
 9. All pullers must go through inspection & have weight slip before registering.
 10. Anything that falls off the tractor before the pin is pulled, tractor will be disqualified.
- TRACK JUDGES RULING IS FINAL ON ALL AREAS OF DISPUTE NOT COVERED IN THESE RULES!**

Stock Farm Class

Any year 6500, 7500, 8500, 9500, 10500, 12500, 14500

1. Must be a "farm" tractor, for example, original frame, rear-end, trans, pto, etc.

Installed & working.

2. Stock injection pump, Stock Turbo, tractor must be factory equipped with turbo.
3. No water injection.
4. Stock Engine RPM'S only!
5. 20.8 max width no cut, or sharpened tires! (True road worn is okay!)
6. No 4wd or front assists unless tractor is unhooked or turned off.
7. TA's, shift on the go is okay.
8. No Alcohol must run on gasoline, LP or diesel. Must run the fuel it was original designed for.
9. Paced

Improved Farm Class

Any year 6500, 7500, 8500, 9500, 10500, 12500, 14500

1. Turbo- limited to single turbo, no larger than 2.8 on inlet (no 3' chargers, no Bigfoot exhaust housing)
2. 3000 RPM Max! Anyone caught over will be disqualified.
3. 20.8 max width tire size, any cut is okay.
4. **ALL TRACTORS MUST HAVE SAFETY EQUIPMENT** – Wheelie bars, air shut-off, fire extinguisher, cross bolts in exhaust is strongly recommended, 2 3/8 bolts, 90° x 1" apart, no more than 10" from turbo outlet.
5. No alcohol must run fuel tractor was originally designed for.
6. No component tractors must run an AG. rear end.
7. No rain caps or curved exhaust pipes (vertical discharge only)
8. All tractors will be teched and must remain in staging area prior to being hooked!

CLASSES ARE SUBJECT TO CHANGE DAY OF PULL!